

IMAGE



SPECIFICATION

Upholstery available in fabric or leather
 Available C.O.M. / C.O.L.

Required Fabric For Upholstery: 0,83 Lm / 2.72 ft
 Required Leather For Upholstery: 1,45 Sq m / 15.61 ft²

Gross Weight: 23,10 Kg / 50.93 lb
 Volume: 0,43 m³ / 15.19 ft³
 Box Dimensions: w 710 x d 710 x h 860 mm / w 27.95" x d 27.95" x h 33.86"
 1 per box
 HARMONIZED SYSTEM CODE 94013900

ROUGH-IN DRAWING



STANDARD FEATURES

INNER FRAME

Double radius stratified curved beech plywood, warm shaped, 16 mm thickness.

PADDING

Cold-moulded polyurethane flexible foams, elasticity to the highest degree, non-deformability and comfort, 40 kg/m³ of density of the shell and the seat. CFC-free moulded foam.

BASE

Stainless sheet steel flat round base, 470 mm diameter, with column and gas lift, swivel, adjustable height. Chromed plate seat support column and gas adj. with curved shape footrest. Stability guaranteed by counterweight. The column is made of Ø40 mm chromed tube, while the base measures 470 mm with counterweight, and is made of 80/10 sheet metal in compliance with UNI EN10130/92. The counterweight cover is made of stainless sheet steel in compliance with UNI EN10130/92.

Attention: gas lift is always chromed

Available FSC® certified

COUNTRY OF PRODUCTION:

Italy

ENVIRONMENT:

Indoor

WARRANTY:

5 years

OTHERS

-Stitching's Are Made With Continuous Filament Polyester Thread With A Water Repellent Finish Made By Coats® Type Weverbird™ This Type Of Lubricated Polyester (Tkt 010) Thread Make The Stitching Stronger, Resistant To The Abrasion, And Gives The Product More Tailoring Appearance. Allowing To Read The Forms And Design Of The Product
 -All screws and assembly systems used in the production of Sitia's product are UNI EN ISO 9001-2000 and UNI ISO/TS 16949 process certified

Sitia srl Copyright 2023/2024 - all rights reserved. The described data could be modified without prior communication