

IMAGE



MODEL BEAUTE'
**DESIGN PERGENTINO BATTOCCHIO &
FIORENZO DORIGO**
ITEM CODE BEA-B ("S" BASE)

SPECIFICATION

Upholstery Available In Fabric or Leather
Available C.O.M. / C.O.L.

Required Fabric For Upholstery: 1,60 Lm / 5.25 ft²
Required Leather For Upholstery: 2,75 Sq m / 29.60 ft²

Gross Weight: 23.70 Kg / 52.25 lb
Volume: 0,35 Cbm / 12.36 ft³
Box Dimensions: w 750 x d 710 x h 460/950 mm / w 29.53" x d 27.95" x
h 18.11/37.40"
1 per box
HARMONIZED SYSTEM CODE 94013900

ROUGH-IN DRAWING



STANDARD FEATURES

INNER FRAME

Seat and backrest made of double radius stratified curved beech plywood, warm shaped, 16 mm thickness.

PADDING

Polyurethane resin ELAST PERFORMANCE characterized by "smart memory", that allows the armchair to recover the initial support even after long and strong pressure. Seat density 40 Kg/mc EM 5 mm thickness, plus D75SR non-deformable, backrest density 35 Kg/mc SE elastic non-deformable, Arm pad density 35 Kg/mc SE. Wadding on seat 250 gr/Sq m, on backrest 380 gr/Sq m +V, rear backrest 200 gr/Sq m + V. CFC-free.

BASE

Swivel base, five-spoke, polished aluminium, diameter 700 mm. (Lead is present in the aluminum to a lesser extent <0.20%, The aluminum used complies with 2005/95/CE, 2002/69/CE and 2003/108/CE). Recyclability 100%.

ARMREST

Multifunctional die-cast polished aluminum arm – adj. 4d. 100 mm height adjustment by the button, pad rotation in three positions or 180° by the button, 40 mm Pad translation, 45 mm width regulation. Depth adjustment 25 mm extension more by each side. Soft touch arm-pad.

MECHANISM

Synchronized mechanism with 100 mm backrest offset 5 locking positions 22° tilt of backrest 11° Seat tilt Wider spring: from 40 to 120 Kg Improved rotation point Wider backrest tilt : 22°. Side tension regulation.

The mechanism is:

- certified ISO 21015:2007, EN and BIFMA;
- certified for 24 hour use and maximum weight of 150 kilo, in accordance with the norm BS 5459: Part 2:2000;
- complies with USA Lead Paint Norm, 16 CFR Part 1303 12/21/2008. Adjustable backrest height 60 mm that allows a correct lumbar support to minimize stress to your backrest and lumbar discs.

GAS LIFT

Pneumatic seat height adjustment, Gas lift column, CLASS 4 DIN 455, chromium plated cone.

CASTORS

Ø 60 mm Tyre Black, Without Brake, suitable for any type of flooring, thanks to the polyurethane rubber.

Available FSC® certified

COUNTRY OF PRODUCTION:

Italy

ENVIRONMENT:

Indoor

WARRANTY:

5 years

OTHERS

- Stitching's Are Made With Continuous Filament Polyester Thread With A Water Repellent Finish Made By Coats® Type Weaverbird™ This Type Of Lubricated Polyester (Tkt 010) Thread Make The Stitching Stronger, Resistant To The Abrasion, And Gives The Product More Tailoring Appearance. Allowing To Read The Forms And Design Of The Product
- All screws and assembly systems used in the production of Sitia's product are UNI EN ISO 9001-2000 and UNI ISO/TS 16949 process certified.