

IMAGE



SPECIFICATION

Upholstery Available In Fabric or Leather
 Available C.O.M. / C.O.L.

Required Fabric For Upholstery: 1,65 Lm / 5. 41 ft
 Required Leather For Upholstery: 2,97 Sq m / 31.97ft²

Gross Weight: 18,50 Kg / 40.79 lb
 Volume: 0,62 Cbm / 21.90 ft³
 Box Dimensions: w 820 x 820 x h 935 mm / w 32.28" x d 32.28" x h 36.81"
 1 per box
 HARMONIZED SYSTEM CODE 94017100

ROUGH-IN DRAWING



STANDARD FEATURES

INNER FRAME

Shaped frame in bent rod-welded steel 16 mm, drowned in cold-moulded polyurethane flexible foams.

PADDING

Cold-moulded polyurethane flexible foams, elasticity to the highest degree, non-deformability and comfort, 40 kg/m³ of density of the shell, 25 kg/m³ of density of the seat separate from the shell. CFC-free molded foam.
 Wadding on seat 180 gr/Sq m.

BASE

Frame in bent wire-welded steel round Ø 16 mm FE360 E4FT-A6 CR.

GLIDES

Anti-slip polyurethane rubber glides covered by a steel-sheet, chromium plated, assembled suitable for any type of flooring.

Available FSC® certified

COUNTRY OF PRODUCTION:

Italy

ENVIRONMENT:

Indoor

WARRANTY:

5 years

OTHERS

-Stitching's Are Made With Continuous Filament Polyester Thread With A Water Repellent Finish Made By Coats® Type Weaverbird™ This Type Of Lubricated Polyester (Tkt 010) Thread Make The Stitching Stronger, Resistant To The Abrasion, And Gives The Product More Tailoring Appearance. Allowing To Read The Forms And Design Of The Product
 -All screws and assembly systems used in the production of Sitia's product are UNI EN ISO 9001-2000 and UNI ISO/TS 16949 process certified.

Sitia srl Copyright 2023/2024 - all rights reserved. The described data could be modified without prior communication